


Field Notes of the NORTH and WEST lines of

Section 36, T 2 N, R 8 W, S.F.M.



T 2 N., R 8 W., S.B.M.

From the established corner to Secs 1, 2, 35 and 36, on the S bdy of the Tp., I run

NORTH between Secs 35 and 36.

Var 14 26 E.

Descending.

Ravine 20 lks wide, course SE and ascend.

22 00 Set granite stone 19x11x9 ins 14 ins in the ground for 4 sec cor mkd 40 00 on W face and raised md of stone alongside. Pits impracticable. Top of ridge bears N 5° W and SE. Thence

44 00 Along east slope of ridge.

75 00

Summit of ridge bears NE and SW, and descend.
Set sandstone 14x9x8 ins 9 ins in the ground for cor to Secs 25, 26,
35 and 36 mkd with 1 notch on E and S edges, and raised a md of
stone alongside. Pits impracticable. Land mountainous. Soil 2nd rate
Timber of pine and oak in ravines. Dense undergrowth of chaparral. 80 00

> EAST on a RANDOM LINE between Secs 25 and 36. Var 14° 26½ E.

Set temporary & section corneb. 40 00

80 27 Intersect E bdy at 69 lks N of corner to Secs 25, 30, 31 and 36, which is a white granite stone 36x12x12 ins 27 ins in the ground mkd with 1 notch on S and 5 notches on N edges, with md of stons alongside. Thence I run

N. 89° 31' W, on a TRUE LINE between Secs 25 and 36, same Var.

Descend.

10 00 Enter San Antonio Canyon, course S.

San Antonio Creek 25 1ks wide, course S. 19 50

27 60 37 20 Leave canyon, course S and ascend.

Trail bears NE and SW.

40 14 Set sandstone 14x9x7 ins 9 ins in the ground for 1/2 sec cor mkd 1/2 on N face and raised a md of stone alongside. Pits impracticable.

79 00 Top of ridge bears NE and SW, and descend.

The corner to Sections 25, 26, 35 and 36. Land mountainous. Soil 1st and 2nd rate. 80 27 Timber Sycamore and pine and oak in canyon. Dense undergrowth of chaparral; brush on each side of canyon.

Surveyed by G. W. Pearson, Deputy Surveyor,

Contract dated December 10, 1883.